

L50 Series Beacons

CERTIFIED, ULTRA BRIGHT COMPACT SUPER-LED® BEACON



Small, Compact, Super-LED beacon featuring exclusive Broadband Energy Radiator™ LED technology which rivals strobe in intensity and draws far less power.



optional MIRROR15 mirror mount bracket.

Available flash patterns

SignalAlert™ 75	Phase 1
SignalAlert 75	Phase 2
CometFlash® 75	Phase 1
CometFlash 75	Phase 2
DoubleFlash 75	Phase 1
DoubleFlash 75	Phase 2
SingleFlash 75	Phase 1
SingleFlash 75	Phase 2
ComAlert™ 75	Phase 1
ComAlert 75	Phase 2
LongBurst™ 75	Phase 1
LongBurst 75	Phase 2
PingPong™ 75	Phase 1
PingPong 75	Phase 2
Single 60	
Single 90	
Single 120	
Single 300	
DoubleFlash 150	
ComAlert 150	
ActionFlash™ 1	
ActionFlash 2	
ModuFlash™	
ActionScan™	
Steady	

FEATURES 1

- SAE Class 1 Certified -L51, SAE Class 2 Certified -L52.
- LED light source has a rated life of 100,000 hours, exceeding that of comparable flash tubes by more than 50:1.
- Low current draw:
L51: 1.5 A peak/ 0.6 A avg.
L52: 0.75 A peak/ 0.3 A avg.
- 75 SignalAlert™ flashes per minute, standard, 25 total selectable flash patterns plus steady-burn capability.
- Permanent mount supplied with four 6" pigtails (Scan-Lock™ and sync wire).
- Magnet mount supplied with 10' cord with cigar plug and On/Off switch with LED "On" indicator.
- Polycarbonate dome and permanent mount base.
- 12 VDC, for 24 VDC models contact factory.
- Five year warranty.
- Size: 3-3/4" (95mm) H x 5" (127mm) Dia.
- Magnetic and magnetic/suction-mount models do not include Scan-Lock.

MODELS

- L51*P.....Class 1, permanent mount
- L51*M.....Class 1, magnet mount

- L52*P.....Class 2, permanent mount
- L52*M.....Class 2, magnet mount

OPTIONS

- MIRROR15...West coast mirror mount bracket
- BBKT15.....Stainless steel shelf mount bracket mounts to flat vertical surface

REPLACEMENT PARTS

- D1500AAmber dome
- D1500CClear dome

*Replace asterisk in model number with desired color. A=Amber, C=White

NOTE: The use of any magnetically mounted warning device on the outside of a vehicle in motion is not recommended and is at the sole risk and responsibility of the user

WHELEN®
ENGINEERING COMPANY, INC.

51 Winthrop Road
Chester, Connecticut 06412-0684
(860) 526-9504 • Fax: (860) 526-4078
www.whelen.com

Whelen Engineering reserves the right to upgrade and improve products without notice.
© 2010 Whelen Engineering Company, Inc. Printed in U.S.A.
NASCAR® is a registered trademark of the National Association for Stock Car Auto Racing, Inc.
Code No. 12128C - 03/10